





Product Type: Plug-in terminal-Plug

Product Name:MC-  
RD5.08H18P-0001

Product Description: Pitch:5.08mm Rated  
Voltage : 320V Rated Current:8A Connection  
method : Push in connection  
colour : customizable

### Product Size



### Parameters

|                         |                    |
|-------------------------|--------------------|
| ⌘ SUPU ID               | MC-RD5.08H18P-0001 |
| ⌘ Pitch                 | 5.08               |
| ⌘ Number of connections | 18                 |
| ⌘ Connection method     | Push in connection |

|                               |                                  |
|-------------------------------|----------------------------------|
| ☞ Protection Level            | IP20                             |
| ☞ Operating temperature range | -40~+105°C                       |
| ☞ Insulation material         | PA66                             |
| ☞ Insulation material group   | I                                |
| ☞ Contact material            | Copper alloy                     |
| ☞ Contact plating             | Sn,Plated                        |
| ☞ Color                       | Green/Black/Blue/Grey/Orange/Red |

## Technical data

|                                                 |                         |
|-------------------------------------------------|-------------------------|
| ☞ IEC Rated Current                             | 8A                      |
| ☞ IEC Rated Voltage                             | 320V                    |
| ☞ Overvoltage category                          | III/III/ II             |
| ☞ Degree of pollution                           | 3 2 2                   |
| ☞ Rated impulse voltage                         | 4KV 4KV 4KV             |
| ☞ UL Rated Current                              | 8A - 8A                 |
| ☞ UL Rated Voltage                              | 300V - 300V             |
| ☞ Conductor cross section rigid                 | 0.2-1.5mm <sup>2</sup>  |
| ☞ Conductor cross section flexible              | 0.2-1.5mm <sup>2</sup>  |
| ☞ Conductor cross section flexible,with furrule | 0.25-1.0mm <sup>2</sup> |
| ☞ Locking screw Specification                   | -                       |
| ☞ Locking screw torque                          | -                       |
| ☞ Fixed Screw Specification                     | -                       |
| ☞ Stripping length                              | 8-9mm                   |
| ☞ Use group                                     | B/C/D                   |

## Ningbo SUPU Electronics Co., Ltd.

Address: No. 150, Xinxing 4th Road, High-tech Industrial Development Zone,  
Cixi City, Zhejiang Province, China

Zip code: 315303

Switchboard: +86 574-63288158

Fax: +86 574-63288170

E-mail:supucontact@supu.cn

Service Hotline: 400-626-6336



Wechat